



	<i>Fluid 7+</i>	<i>Fluid 9</i>	<i>Fluid 7</i>
Available Frame Sizes	XS, S, M, L, XL	S, M, L, XL	XS, S, M, L, XL
Headset Type	Internal Tapered	Internal Tapered	Internal Tapered
S.H.I.S	ZS44/28.6   ZS56/40	ZS44/28.6   ZS56/40	ZS44/28.6   ZS56/40
Upper Headset Diameter [mm]	44	44	44
Lower Headset Diameter [mm]	56	56	56
Lower Headset Stack [mm]	3.2	3.2	3.2
Fork Length (MAX)/Offset		582/51	507/42
BB Type/Width	BSA/73	BSA/73	BSA/73
Max Chaining Size 1x 2x 3x	30 28/38 24/32/44	30 28/38 24/32/44	30 28/38 24/32/44
OLD [mm]	141	135	135
Rear Axle Type/Length/Thread Length/Thread	10mm QR	10mm QR	10mm QR
Rear Derailleur Hanger	959375-15	959375-15	959375-15
Rear Brake Mount	160mm Post	160mm Post	160mm Post
FD type	NA	HDM bottom Pull	High Clamp Top Pull
Seatpost Size [mm]	30.9	30.9	30.9
Seatpost Clamp size [mm]	34.9	34.9	34.9
Max Tire Size [in]	650Bx2.8	29x2.2	650Bx2.2
Waterbottle mounts [#]	1	1	1
ISCG 05 Mounts	No	No	No
Guides for Adj Seatpost	Yes	Yes	Yes
Rear Wheel Travel [mm]	120	120	120
Starting Leverage Ratio	2.9	2.9	2.92
Finishing Leverage Ratio	2.6	2.5	2.44
Average Leverage Ratio	2.7	2.7	2.7
Shock length [mm/in]	184/7.25	184/7.25	184/7.25
Shock Stroke [mm/in]	44/1.75	44/1.75	44/1.75
Linkarm Shock Spacers [W*ID, mm]	40x8	40x8	40x8
Frame Shock Spacers [W*ID, mm]	22.2*8	22.2*8	22.2*8
Shock orientation	Air can up	Air can up	Air can up
Spring Rate [lbs/in]	N/A	N/A	N/A

	<i>Fluid 7+</i>	<i>Fluid 9</i>	<i>Fluid 7</i>
<b>Shock 1</b>	Fox Float DPS Comp - L, Rebound - L, Climb - L, SV eyelet Vol Spac - 0	Fox Float DPS Comp - L, Rebound - L, Climb - L, SV eyelet Vol Spac - 0	Fox Float CTD Evolution Comp - Light, Reb - M, Climb - Firm, SV air can
<b>Shock 2</b>	RockShox Monarch RL Open Comp - M, Lock Comp - 430, Reb - M HVI eyelet w/ no spcra	RockShox Monarch RL Open Comp - M, Lock Comp - 430, Reb - M HVI eyelet w/ no spcra	RockShox Monarch RL Open Comp - L, Lock Comp - 430, Reb - M HVI eyelet w/ no spcra
<b>Recommended Sag (%)</b>	25	25	25
<b>BB Pivot Bearing [ID*OD*W mm]</b>	15*28*7 (6902) x 2	15*28*7 (6902) x 2	15*28*7 (6902) x 2
<b>BB Pivot [Qty in pkg]</b>	959800-13-247	959800-13-247	959800-13-247
<b>Dropout Bearing [ID*OD*W mm]</b>	8*22*7 (608) x 2	8*22*7 (608) x 2	8*22*7 (608) x 2
<b>Dropout Pivot [Qty in pkg]</b>	959800-13-248	959800-13-248	959800-13-248
<b>SS/Linkarm Bearing [ID*OD*W mm]</b>	8*22*7 (608) x 2	8*22*7 (608) x 2	8*22*7 (608) x 2
<b>SS/Linkarm Pivot [Qty in pkg]</b>	959800-13-246	959800-13-246	959800-13-246
<b>Linkarm Bearing [ID*OD*W mm]</b>	12*24*6 (6901) x 2	12*24*6 (6901) x 2	12*24*6 (6901) x 2
<b>Linkarm Pivot [Qty in pkg]</b>	959800-13-246	959800-13-246	959800-13-246
<b>Shock Hardware at Linkarm PN [Qty in pkg]</b>	959800-13-245	959800-13-245	959800-13-245
<b>Shock Hardware at Mainframe PN</b>	959800-13-244	959800-13-244	959800-13-244