



	OPTIC C9	OPTIC C7
Available Frame Sizes	S, M, L, XL	XS, S, M, L, XL
Headset Type	Integrated Tapered	Integrated Tapered
S.H.I.S	IS42/28.6 IS52/40	IS42/28.6 IS52/40
Upper Headset Diameter [mm]	42	42
Lower Headset Diameter [mm]	52	52
Lower Headset Stack [mm]	1	1
Fork Length (MAX)/Offset	528/51	538/44
BB Type/Width	PF92 (41mmID)/92	PF92 (41mmID)/92
Max Chaining Size 1x 2x 3x	S34, M36, L&XL38 28/36 NA	XS34, S36, M,L&XL38 28/36 NA
OLD [mm]	148	148
Rear Axle Type/Length/Thread Length/Thread	TA12/L174/TL20/M12x1.75 Maxle 142 913105-003	TA12/L174/TL20/M12x1.75 Maxle 142 913105-003
Rear Derailleur Hanger	carbon seatstay 913015-003 alloy seatstay 913015-002	carbon seatstay 913015-003 alloy seatstay 913015-002
Rear Brake Mount	160mm Post	160mm Post
FD clamp size [mm]	N/A	N/A
FD type	S3 Mount (e-Type no plate)	S3 Mount (e-Type no plate)
Seatpost Size [mm]	31.6	30.9
Seatpost Clamp size [mm]	915000-002 [34.9]	915000-002 [34.9]
Max Tire Size [in]	650Bx2.4	650Bx2.4
Waterbottle mounts [#]	1	1
ISCG 05 Mounts	Yes 915700-001 (w/FD mount) 915700-002 (w/o FD mount)	Yes 915700-001 (w/FD mount) 915700-002 (w/o FD mount)
Guides for Adj Seatpost	Yes	Yes
Rear Wheel Travel [mm]	110	120
Starting Leverage Ratio	2.3	2.5
Finishing Leverage Ratio	2.1	2.2
Average Leverage Ratio	2.2	2.3
Shock length [mm/in]	190/7.5	190/7.5
Shock Stroke [mm/in]	51/2.0	51/2.0
Linkarm Shock Spacers [W*ID, mm]	40*8	40*8
Frame Shock Spacers [W*ID, mm]	22.2*8	22.2*8
Shock orientation	Air Can up	Air Can up
Spring Rate [lbs/in]	NA	NA

	OPTIC C9	OPTIC C7
Shock 1	Fox Float DPS Comp - XL, Rebound - M Climb - L, SV Evol eyelet Vol Spac - 0	Fox Float DPS Comp - L, Rebound - M Climb - L, SV Evol eyelet Vol Spac - 0
Shock 2	Rockshox Monarch RT Rebound - M, Open Comp - L, Lock	Rockshox Monarch RT Rebound - M Open Comp - L, Lock
Shock 3	Rockshox Monarch RT3 Rebound - M, Open Comp - L, Mid Comp - Soft, Lock Comp - 320, Vol - Debonair Vol Spac - 2	Rockshox Monarch RT3 Rebound - M, Open Comp - L, Mid Comp - Soft, Lock Comp - 320, Vol - Debonair Vol Spac - 2
Recommended Sag (%)	30	30
BB Pivot Bearing [ID*OD*W mm]	12*24*6 6190 X 2	12*24*6 6190 X 2
BB Pivot [Qty in pkg]	913600-008 - shaft & nut 913300-010 - spacers 913200-6901 - bearings	913600-008 - shaft & nut 913300-010 - spacers 913200-6901 - bearings
Dropout Bearing [ID*OD*W mm]	10*19*5 6180 X 4	10*19*5 6180 X 4
Dropout Pivot [Qty in pkg]	913500-007 - Shafts 913300-008 - 2mm spacers 913300-009 - 3.5mm spacers 913200-6800 - bearings	913500-007 - Shafts 913300-008 - 2mm spacers 913300-009 - 3.5mm spacers 913200-6800 - bearings
SS/Linkarm Bearing [ID*OD*W mm]	12*24*6 6190 X 2	12*24*6 6190 X 2
SS/Linkarm Pivot [Qty in pkg]	913500-008 - shafts 913300-010 - spacers 913200-6901 - bearings	913500-008 - shafts 913300-010 - spacers 913200-6901 - bearings
Linkarm Bearing [ID*OD*W mm]	12*24*6 6190 X 2	12*24*6 6190 X 2
Linkarm Pivot [Qty in pkg]	913600-007 - shaft & bolt 913300-010 - spacers 913200-6901 - bearings	913600-007 - shaft & bolt 913300-010 - spacers 913200-6901 - bearings
Shock Hardware at Linkarm PN [Qty in pkg]	913600-006 Shaft & Bolt	913600-006
Shock Hardware at Mainframe PN	913600-005	913600-005
Cable Guide Single Small Tube[Qty]	914100-001 [2]	914100-001 [2]
Internal Port Double [Qty]	914100-015 [2]	914100-015 [2]
Internal Port Triple [Qty]	914100-016 [2]	914100-016 [2]
Internal Port 4mm plug [Qty]	914100-017 [2]	914100-017 [2]
Internal Port blank plug [Qty]	914100-018 [5]	914100-018 [5]
CS Protector	915200-007	915200-007
Seatstay Protector	915300-001	915300-001