



	RANGE CARBON	RANGE ALLOY
Available Frame Sizes	S, M, L, XL	XS, S, M, L, XL
Headset Type	Integrated Tapered	Internal Tapered
S.H.I.S	IS42/28.6 IS52/40	ZS44/28.6 ZS56/40
Upper Headset Diameter [mm]	42	44
Lower Headset Diameter [mm]	52	56
Lower Headset Stack [mm]	1	3.2
Fork Length (MAX)/Offset [mm]	562/42	562/42
BB Type/Width	PF92 (41mmID)/92	BSA/73
OLD [mm]	142	142
Rear Axle Type/Length/Thread Length/Thread	Syntace X-12	TA12/L174/TL20/M12x1.75
Rear Derailleur Hanger	959375-15-3	959375-15-2
Rear Brake Mount	160mm Post	160mm Post
FD clamp size [mm]	N/A	NA
FD type	HDM Top Pull	HDM Top Pull
Seatpost Size [mm]	30.9	30.9
Seatpost Clamp size [mm]	34.9 95064770-14-02	34.9
Max Tire Size [in]	650Bx2.4	650Bx2.4
Waterbottle mounts [#]	1	1
ISCG 05 Mounts	Yes	Yes
Guides for Adj Seatpost	Yes	Y & Stealth port
Extra Syntace Bolt	Yes	NA
Rear Wheel Travel [mm]	160	160
Starting Leverage Ratio	2.8	2.8
Finishing Leverage Ratio	2.3	2.2
Average Leverage Ratio	2.5	2.5
Shock length [mm/in]	216/8.5	216/8.5
Shock Stroke [mm/in]	63/2.5	63/2.5
Linkarm Shock Spacers [W*ID, mm]	40*10	40.0*10
Frame Shock Spacers [W*ID, mm]	22.2*10	22.2*10
Shock orientation	RS Air Can up, CC Air Can down	Air Can up
Spring Rate [lbs/in]	N/A	NA

	RANGE CARBON	RANGE ALLOY
Shock 1	Cane Creek DB Air CS XV Air Sleeve, 2 large vol spcrrs	Fox Float CTD Evolution Velocity - L, Reb - M, XV sleeve w/ 0.2 Spacer
Shock 2	RockShox Monarch Plus RC3 Reb - M, Comp - L, Vol - Debonair w/ no spacers	X-Fusion O2R A-Tune (soft) AV Sleeve
Shock 3	RockShox Monarch Plus R Reb - M, Comp - L, Vol - High Vol w/ no spacers	N/A
Shock 4	X-Fusion O2R A-Tune (soft) AV Sleeve	N/A
Recommended Sag (%)	30	30
BB Pivot Bearing [ID*OD*W mm]	20*32*7 (6804) x 2	15*28*7 6902 x 2
BB Pivot Parts	959800-13-242	959800-15-220
Dropout Bearing [ID*OD*W mm]	10*19*5 (6800) x 4	10*19*5 6800 x 4
Dropout Pivot Parts	959800-14-243 or 959800-14-237	913500-013 shaft 913300-002 2mm spacers (2) 913300-001 4mm spacers (2) 913200-6901-EM bearings (2)
SS/Linkarm Bearing [ID*OD*W mm]	10*22*6 (6900) x 2	10*22*6 6900 x 2
SS/Linkarm Pivot Parts	959800-13-241	959800-15-219
Linkarm Bearing [ID*OD*W mm]	15*28*7 (6902) x 2	15*28*7 6902 x 2
Linkarm Pivot Parts	959800-13-239	959800-15-217
Shock Hardware at Linkarm PN	959800-13-240	959800-15-218
Shock Hardware at Mainframe PN	959800-13-238	959800-15-216
Cable Guide Single Big Tube[Qty]	959800-15-200-1 [1]	959800-15-200-1 [4]
Cable Guide Single Small Tube[Qty]	959800-15-200 [1]	959800-15-200
Cable Guide Double [Qty]	NA	959800-15-200-2 [3]
Cable Guide Triple [Qty]	NA	959800-15-200-3 [0]
Internal Cable Port	95064825-14-4 [7]]	NA
Internal Cable 4mm Grommet	95064825-14-2[4]	NA
Internal Cable 5mm Grommet	95064825-14-4[3]	NA
Internal Cable Port Cover	95064825-14-5 [2]	NA
Lower DT Protector	95064770-14-1	NA
CS Protector	95064770-14-01	95064770-14-01