



	SIGHT CARBON	SIGHT ALLOY
Available Frame Sizes	S, M, L, XL	XS, S, M, L, XL
Headset Type	Integrated Tapered	Internal Tapered
S.H.I.S	IS42/28.6 IS52/40	ZS44/28.6 ZS56/40
Upper Headset Diameter [mm]	42	44
Lower Headset Diameter [mm]	52	56
Lower Headset Stack [mm]	1	3.2
Fork Length (MAX)/Offset [mm]	529/42	529/42
BB Type/Width	PF92 (41mmID)/92	BSA/73
OLD [mm]	142	142
Rear Axle Type/Length/Thread Length/Thread	Syntace X-12	TA12/L174/TL20/M12x1.75
Rear Derailleur Hanger	959375-15-3	959375-15-2
Rear Brake Mount	160mm Post	160mm Post
FD clamp size [mm]	N/A	NA
FD type	HDM Top Pull	HDM Top Pull
Seatpost Size [mm]	30.9	30.9
Seatpost Clamp size [mm]	34.9 95064770-14-02	34.9
Max Tire Size [in]	650Bx2.4	650Bx2.4
Waterbottle mounts [#]	1	1
ISCG 05 Mounts	Yes	Yes
Guides for Adj Seatpost	Yes	Y & Stealth port
Extra Syntace Bolt	Yes	NA
Rear Wheel Travel [mm]	140	140
Starting Leverage Ratio	2.6	2.6
Finishing Leverage Ratio	2.2	2.2
Average Leverage Ratio	2.5	2.5
Shock length [mm/in]	200/7.875	200/7.875
Shock Stroke [mm/in]	57/2.25	57/2.25
Linkarm Shock Spacers [W*ID, mm]	40*10	40.0*10
Frame Shock Spacers [W*ID, mm]	22.2*10	22.2*10
Shock orientation	RS & Fox Air Can up, CC Air Can down	Air Can up
Spring Rate [lbs/in]	N/A	NA

	SIGHT CARBON	SIGHT ALLOY
Shock 1	Cane Creek DB Inline High Volume Sleeve	Fox Float CTD Performance Velocity - L, Rebound - M, Climb - Firm, XV eyelet w/ 0.4 spacer, 250psi BV
Shock 2	Fox Float CTD Performance Velocity - L, Rebound - M, Climb - Firm, XV eyelet w/ 0.4 spacer, 250psi BV	RockShox Monarch RL Comp - L, Rebound - M, HV air sleeve
Shock 3	RockShox Monarch RL Comp - L, Rebound - M, HV air sleeve	X-Fusion O2R A-Tune (soft) AV Sleeve
Shock 4	N/A	N/A
Recommended Sag (%)	30	30
BB Pivot Bearing [ID*OD*W mm]	20*32*7 (6804) x 2	15*28*7 6902 x 2
BB Pivot Parts	959800-13-242	959800-15-220
Dropout Bearing [ID*OD*W mm]	10*19*5 (6800) x 4	10*19*5 6800 x 4
Dropout Pivot Parts	959800-13-243	959800-15-221
SS/Linkarm Bearing [ID*OD*W mm]	10*22*6 (6900) x 2	10*22*6 6900 x 2
SS/Linkarm Pivot Parts	959800-13-241	959800-15-219
Linkarm Bearing [ID*OD*W mm]	15*28*7 (6902) x 2	15*28*7 6902 x 2
Linkarm Pivot Parts	959800-13-239	959800-15-217
Linkarm Shock Hardware PN	959800-13-240	959800-15-218
Frame Shock Hardware PN	959800-13-238	959800-15-216
Cable Guide Single Big Tube[Qty]	959800-15-200-1 [1]	959800-15-200-1 [4]
Cable Guide Single Small Tube[Qty]	959800-15-200	959800-15-200
Cable Guide Double [Qty]	NA	959800-15-200-2 [3]
Cable Guide Triple [Qty]	NA	959800-15-200-3 [0]
Internal Cable Port	95064825-14-4 [7]	NA
Internal Cable 4mm Grommet	95064825-14-2[4]	NA
Internal Cable 5mm Grommet	95064825-14-4[3]	NA
Internal Cable Port Cover	95064825-14-5 [2]	NA
Lower DT Protector	95064770-14-1	NA
CS Protector	95064770-14-01	95064770-14-01