



	FLUID 9	FLUID 6
Available Frame Sizes	S, M, L, XL	XXS
Headset Type	Internal Tapered	Internal
S.H.I.S	ZS44/28.6 ZS56/40	ZS44/28.6 ZS44/30
Upper Headset Diameter [mm]	44	44
Lower Headset Diameter [mm]	56	44
Lower Headset Stack [mm]	3.2	3.2
Fork Length (MAX)/Offset	582/51	493/39
BB Type/Width	BSA/73	BSA/73
Max Chainring Size 1x 2x 3x	30 28/38 24/32/44	30 28/38 24/32/44
OLD [mm]	135	135
Rear Axle Type/Length/Thread Length/Thread	10mm QR	10mm QR
Rear Derailleur Hanger	959375-15	959375-15
Rear Brake Mount	160mm Post	160mm Post
FD clamp size [mm]	NA	34.9
FD type	HDM bottom Pull	Low Clamp Bottom Pull
Seatpost Size [mm]	30.9	30.9
Seatpost Clamp size [mm]	34.9	34.9
Max Tire Size [in]	29x2.2	26x2.2
Waterbottle mounts [#]	1	0
ISCG 05 Mounts	No	No
Guides for Adj Seatpost	Yes	Yes
Extra Syntace Bolt	N/A	N/A
Rear Wheel Travel [mm]	120	120
Starting Leverage Ratio	2.9	2.92
Finishing Leverage Ratio	2.5	2.6
Average Leverage Ratio	2.7	2.7
Shock length [mm/in]	184/7.25	184/7.25
Shock Stroke [mm/in]	44/1.75	44/1.75
Linkarm Shock Spacers [W*ID, mm]	40x8	40x8
Frame Shock Spacers [W*ID, mm]	22.2*8	22.2*8
Shock orientation	Air can up	Air can up
Spring Rate [lbs/in]	N/A	N/A

	FLUID 9	FLUID 6
Shock 1	Fox Float DPS Comp - L, Rebound - L, Climb - L, SV eyelet, Vol Spac - 0	RockShox Monarch RL Open Comp - M, Lock Comp - 430, Reb - M, HVI eyelet w/ no spcrs
Shock 2	RockShox Monarch RL Open Comp - M, Lock Comp - 430, Reb - M, HVI eyelet w/ no spcrs	NA
Recommended Sag (%)	25	25
BB Pivot Bearing [ID*OD*W mm]	15*28*7 (6902) x 2	15*28*7 (6902) x 2
BB Pivot [Qty in pkg]	959800-13-247	959800-13-247
Dropout Bearing [ID*OD*W mm]	8*22*7 (608) x 2	8*22*7 (608) x 2
Dropout Pivot [Qty in pkg]	959800-13-248	959800-13-248
SS/Linkarm Bearing [ID*OD*W mm]	8*22*7 (608) x 2	8*22*7 (608) x 2
SS/Linkarm Pivot [Qty in pkg]	959800-13-246	959800-13-246
Linkarm Bearing [ID*OD*W mm]	12*24*6 (6901) x 2	12*24*6 (6901) x 2
Linkarm Pivot [Qty in pkg]	959800-13-246	959800-13-246
Shock Hardware at Linkarm PN [Qty in pkg]	959800-13-245	959800-13-245
Shock Hardware at Mainframe PN	959800-13-244	959800-13-244