



RANGE ALLOY	
Available Frame Sizes	XS, S, M, L, XL
Headset Type	Internal Tapered
S.H.I.S	ZS44/28.6   ZS56/40
Upper Headset Diameter [mm]	44
Lower Headset Diameter [mm]	56
Lower Headset Stack [mm]	3.2
Fork Length (MAX)/Offset	562/42
BB Type/Width	BSA/73
Max Chaining Size 1x 2x 3x	XS30, S&M32, L&XL34 28/36 NA
OLD [mm]	142
Rear Axle Type/Length/Thread Length/Thread	TA12/L174/TL20/M12x1.75 Maxle 142 913105-003
Rear Derailleur Hanger	913015-002
Rear Brake Mount	160mm Post
FD clamp size [mm]	NA
FD type	HDM Top Pull
Seatpost Size [mm]	30.9
Seatpost Clamp size [mm]	95064770-14-02 [34.9]
Max Tire Size [in]	650Bx2.4
Waterbottle mounts [#]	1
ISCG 05 Mounts	Yes
Guides for Adj Seatpost	Y & Stealth port
Extra Syntace Bolt	NA
Rear Wheel Travel [mm]	160
Starting Leverage Ratio	2.8
Finishing Leverage Ratio	2.2
Average Leverage Ratio	2.5
Shock length [mm/in]	216/8.5
Shock Stroke [mm/in]	63/2.5
Linkarm Shock Spacers [W*ID, mm]	40.0*10
Frame Shock Spacers [W*ID, mm]	22.2*10
Shock orientation	Air Can up
Spring Rate [lbs/in]	NA

RANGE ALLOY	
Shock 1	Fox Float CTD Evolution Velocity - L, Reb - M XV sleeve w/ 0.2 Spacer
Shock 2	X-Fusion O2R A-Tune (soft) AV Sleeve
Shock 3	NA
Shock 4	NA
Recommended Sag (%)	30
BB Pivot Bearing [ID*OD*W mm]	15*28*7 6902 x 2
BB Pivot [Qty in pkg]	959800-15-220
Dropout Bearing [ID*OD*W mm]	10*19*5 6800 x 4
Dropout Pivot [Qty in pkg]	959800-15-221
SS/Linkarm Bearing [ID*OD*W mm]	10*22*6 6900 x 2
SS/Linkarm Pivot [Qty in pkg]	959800-15-219
Linkarm Bearing [ID*OD*W mm]	15*28*7 6902 x 2
Linkarm Pivot [Qty in pkg]	959800-15-217
Shock Hardware at Linkarm PN, [Qty in pkg]	959800-15-218
Shock Hardware at Mainframe PN	959800-15-216
Cable Guide Single Big Tube[Qty Rqd]	914100-002 [4]
Cable Guide Single Small Tube[Qty]	914100-001 [1]
Cable Guide Double [Qty]	959800-15-200-2 [3]
Cable Guide Triple [Qty]	959800-15-200-3 [1]
CS Protector	915200-010