



| SIGHT ALLOY | |
|--|---|
| Available Frame Sizes | XS, S, M, L, XL |
| Headset Type | Internal Tapered |
| S.H.I.S | ZS44/28.6 ZS56/40 |
| Upper Headset Diameter [mm] | 44 |
| Lower Headset Diameter [mm] | 56 |
| Lower Headset Stack [mm] | 3.2 |
| Fork Length (MAX)/Offset | 529/42 |
| BB Type/Width | BSA/73 |
| Max Chaining Size 1x 2x 3x | XS30, S&M32, L&XL34 28/36 NA |
| OLD [mm] | 142 |
| Rear Axle Type/Length/Thread Length/Thread | TA12/L174/TL20/M12x1.75 Maxle 142 913105-003 |
| Rear Derailleur Hanger | 913015-002 |
| Rear Brake Mount | 160mm Post |
| FD clamp size [mm] | NA |
| FD type | HDM Top Pull |
| Seatpost Size [mm] | 30.9 |
| Seatpost Clamp size [mm] | 95064770-14-02 [34.9] |
| Max Tire Size [in] | 650Bx2.4 |
| Waterbottle mounts [#] | 1 |
| ISCG 05 Mounts | Yes |
| Guides for Adj Seatpost | Y & Stealth port |
| Extra Syntace Bolt | NA |
| Rear Wheel Travel [mm] | 140 |
| Starting Leverage Ratio | 2.6 |
| Finishing Leverage Ratio | 2.2 |
| Average Leverage Ratio | 2.5 |
| Shock length [mm/in] | 200/7.875 |
| Shock Stroke [mm/in] | 57/2.25 |
| Linkarm Shock Spacers [W*ID, mm] | 40.0*10 |
| Frame Shock Spacers [W*ID, mm] | 22.2*10 |
| Shock orientation | Air Can up |
| Spring Rate [lbs/in] | NA |

| SIGHT ALLOY | |
|--|--|
| Shock 1 | Fox Float CTD Performance Velocity - L, Rebound - M, Climb - Firm XV eyelet w/ 0.4 spacer, 250psi BV |
| Shock 2 | RockShox Monarch RL Comp - L, Rebound - M, HV air sleeve |
| Shock 3 | X-Fusion O2Rm, A-Tune (soft), AV Sleeve |
| Recommended Sag (%) | 30 |
| BB Pivot Bearing [ID*OD*W mm] | 15*28*7 6902 x 2 |
| BB Pivot [Qty in pkg] | 959800-15-220 |
| Dropout Bearing [ID*OD*W mm] | 10*19*5 6800 x 4 |
| Dropout Pivot [Qty in pkg] | 959800-15-221 |
| SS/Linkarm Bearing [ID*OD*W mm] | 10*22*6 6900 x 2 |
| SS/Linkarm Pivot [Qty in pkg] | 959800-15-219 |
| Linkarm Bearing [ID*OD*W mm] | 15*28*7 6902 x 2 |
| Linkarm Pivot [Qty in pkg] | 959800-15-217 |
| Shock Hardware at Linkarm PN, [Qty in pkg] | 959800-15-218 |
| Shock Hardware at Mainframe PN | 959800-15-216 |
| Cable Guide Single Big Tube[Qty Rqd] | 914100-002 [4] |
| Cable Guide Single Small Tube[Qty] | 914100-001 [1] |
| Cable Guide Double [Qty] | 959800-15-200-2 [3] |
| Cable Guide Triple [Qty] | 959800-15-200-3 [0] |
| CS Protector | 95064770-14-01 |